Housing and Property Chamber First-tier Tribunal for Scotland



Statement of Decision of the Housing and Property Chamber of the First-tier tribunal for Scotland under Section 26 (1) of the Housing (Scotland) Act 2006

HOUSE AT 17 Nether Craigour, Edinburgh, EH17 7SB ("the Property")

Title No: MID108862

Chamber Reference PRHP/RP/16/0362

Ms Sohna Samba Thomas, 17 Nether Craigour, Edinburgh, EH17 7SB ("The Tenant")

Miss Syamala Devi Podarama, 30 Nether Craigour, Edinburgh, EH17 7SB ("The Landlord")

Tribunal Members – George Clark (Legal Member) and Geraldine Wooley (Ordinary Member)

Decision

The First-tier tribunal for Scotland (Housing and Property Chamber) ('the tribunal'), having made such enquiries as it saw fit for the purposes of determining whether the Landlord has complied with the duty imposed by Section 14 (1)(b) in relation to the house concerned, determined that the Landlord had not failed to comply with the duty imposed by Section 14 (1)(b) of the Act.

Background

- By application received on 21 November 2016, the Tenant applied to the Private Rented Housing Panel for a determination of whether the Landlord had failed to comply with the duties imposed by Section 14 (1)(b) of the Housing (Scotland) Act 2006 ("the Act").
- 2. The application stated that the Tenant considered that the Landlord had failed to comply with her duty to ensure that the house meets the repairing standard.

- 3. On 1 December 2016, the jurisdiction of the Private Rented Housing Panel transferred to the Housing and Property Chamber of the First-tier Tribunal for Scotland.
- 4. By letter dated 16 December 2016, the President of the Housing and Property Chamber intimated a decision to refer the application under Section 22 (1) of the Act to a tribunal.
- 5. The tribunal served Notice of Referral under and in terms of Schedule 2, Paragraph 1 of the Act upon the parties.
- 6. By letter dated 10 January 2017, the Tenant's representative advised the tribunal that the Tenant wished to withdraw the application, as the Landlord was attending to the issues she had complained about. The tribunal, however, decided on 16 January 2017, to continue to determine the application as a number of the issues raised by the Tenant in the application, if established, caused significant health and safety risks to any occupant of the Property.
- 7. The tribunal arrived to inspect the Property on the morning of 20 January 2017, but was unable to gain access, as there was no answer when the tribunal members knocked on the door. It appeared that the Tenant was not in the Property. The Landlord was present at the attempted inspection.
- 8. The tribunal comprised George Clark (Legal member) and Geraldine Wooley (Ordinary Member)(surveyor).
- 9. The Landlord advised the tribunal outside the Property that some of the matters referred to in the application had been dealt with and that she had instructed the replacement of the bathroom fittings and tiling, rather than just attempting to replace a small number of broken tiles. This work would be carried out in late February or early March and would take approximately 10 days to complete.
- 10. Following the inspection of the Property the tribunal held a hearing at George House, 126 George Street, Edinburgh. Neither party was present or represented at the hearing.
- 11. Following the hearing, the tribunal determined that a date be set for a further inspection and hearing and issued a Direction requiring the Landlord to provide the tribunal with a current Gas Safety Certificate and a satisfactory Electrical Installation Condition Report in respect of the Property, to include confirmation that the smoke and heat detectors in the Property were in working order and meet current regulations, The tribunal further directed that the central heating system in the Property should be switched on at the time of the further inspection.
- 12. The tribunal inspected the Property on the morning of 27 March 2017. The Tenant admitted the tribunal members to the Property. The Landlord was present at the inspection.

- 13. A file of photographs, taken at the inspection, is attached to and forms part of this Statement of Decision.
- 14. The Tenant, in the application, had stated that there was no Gas Safety Certificate, there were no fire alarms or carbon monoxide detectors in the Property, there was an unsafe glass door with broken knobs, there were electrical issues, damp and mould, sewage and plumbing issues, the Tenant was unable to use the bathroom, there was no extractor fan and tiling in the bathroom was falling off, the fridge freezer was broken, the windows were draughty, the kitchen sink was dripping and there were issues with the roof and the patio.
- 15. The Landlord provided the tribunal, at the inspection, with a current Gas Safety Certificate and an Electrical Installation Condition Report. The central heating system was switched on at the time of the inspection.
- 16. Following the inspection, the tribunal held a hearing at George House, 126 George Street, Edinburgh. The Landlord did not attend the hearing and the Tenant, having withdrawn the application, was not present or represented at the hearing.

Findings of Fact

The tribunal makes the following findings of fact:

- There is in place a current Gas Safety Certificate in respect of the Property. It is dated 22 December 2016. The Customer Checklist indicates that as at 22 December 2016, there was no carbon monoxide monitor in the Property.
- There are smoke detectors in the kitchen, living room and hallway of the Property and a heat detector in the kitchen. They are mains-wired and interlinked.
- There is a carbon monoxide monitor in the hallway, above the hall cupboard that houses the central heating boiler in the Property. There are no gas appliances in the kitchen and no gas fires in the Property.
- The glass doors between the lounge and kitchen of the Property have been replaced with wooden doors.
- The tribunal has seen an Electrical Installation Condition Report in respect of the Property. It is dated 15 March 2017 and was issued by Contract Heating Limited, 2B Bankhead Crossway South, Edinburgh EH11 4EX, a NICEIC registered contractor. It contains one item rated C1, relating to the rear security lighting, but this has been addressed by work specified in 3 Minor Electrical Installation Works Certificates issued by the same company on 24 March 2017. The Report also contained 11 items rated as C2, but the tribunal has seen a receipt from the contractors confirming that all the remedial work has been carried out. The tribunal has also had sight of a Certificate of Design, Installation and Commissioning in respect of the upgrading of the smoke detector system, including replacement of the hall detectors and

- the installation of detectors in the lounge and the kitchen of the Property.
- A completely new bathroom has been installed in the Property and the tiling issue has been resolved.
- The cooker has an extractor fan above it, which was working at the time of the inspection.
- There is no evidence of mould or damp in the Property and the Tenant confirmed at the inspection that the problem had been in the old bathroom which has been replaced.
- The Tenant confirmed at the inspection that the kitchen sink was now operating satisfactorily and that there were no ongoing draught problems with the windows.
- There is no evidence of any repairs issues with the roof or the patio of the Property.
- The central heating was working at the time of the inspection.
- The Tenant confirmed that the fridge freezer in the Property has been replaced.

Reasons for the decision

- 17. The tribunal did not inspect the Property prior to work being carried out to replace the bathroom and move the cooker and prior to the electrical works covered by the Minor Electrical Installation Works Certificates, so did not see the Property in the condition it was at the time of the application, but the tribunal is satisfied that there are no failures to meet the repairing standard in respect of any of the issues set out in the application.
- 18. The decision of the tribunal was unanimous.

C Clark

Right of Appeal

In terms of section 46 of the Tribunals (Scotland) Act 2014, a party aggrieved by the decision of the Tribunal may appeal to the Upper Tribunal for Scotland on a point of law only. Before an appeal can be made to the Upper Tribunal, the party must first seek permission to appeal from the First-tier Tribunal. That party must seek permission to appeal within 30 days of the date the decision was sent to them.

Where such an appeal is made, the effect of the decision and of any order is suspended until the appeal is abandoned or finally determined by the Upper Tribunal, and where the appeal is abandoned or finally determined by upholding the decision, the decision and any order will be treated as having effect from the day on which the appeal is abandoned or so determined.

	O Clark	
Signed Date	27.72rd 2017	Legal Member/Chairperson

This is the file of photographing take at the inspection, refing to the scan of the 27. Tach 2017 G Clark




17 Nether Craigour Edinburgh EH17 7SB Inspection 27 March 2017



1) CO alarm installed outside boiler cupboard in front lobby



2) Fire detection system upgraded – heat alarm in kitchen





4) New fridge-freezer







6) Bathroom replaced





Landlord Gas Safety Record

detailed internal inspection of the Flue integrity, construction and checked for satisfactory evacuation of products of combustion. A Gas Safety (1 & U) Regulations. Flues were inspected visually and lining has not been carried out. The inspection is for gas safety purposes only in accordance with the

> Aylestone Road LE2 7QH Leicestershire Leicester **Landlord Inspection Service**

> > Landlord/Agent Details Property details 30 Nether Craigour Miss Syamala Devi Podarama

EH17 7SB

Edinburgh

Edinburgh EH17 7SB 17 Nether Craigour

GCI ar Scottish Gas

ではのたべい すい

+ 11

HALL CUPBOARD Location CHB Type Appliance details Make Model ROOM-SEALED Flue type Operating (see key below) 31.12k value operation Safety correct device Yes satisfactory Ventilation Yes Flue flow Hue performance N/A test Inspection details Spillage test N/A satisfactory termination of flue and condition Visual Yes Appliance safe Yes Requested to test* Yes unable to ndicate YES if

				V
due within 12 month				4
:				W
				2
Ų	N/A	The second secon		1
Gas installation tightness test and vi inspection of pipew	Labelled and warning notice given	What we've done	Details of any defects we found	

ths cion

visual

This safety record has our engineer's electronic signature:

Engineer name: Jason Browdowski 56095

Date: 22rd December 2016

Job Number: 1361696038

Number of appliances tested: 1

Key for operating Value

* if Requested to test is NO or Unable to test is YES, please take a look at the back of this certificate

be displayed where neither 'm' nor 'k' could c=Combustion Ratio CO/CO 2 ('c' will only I=Gas Rates in Kilowatts (kW) m=Operating Pressure in Millibars (mbars) be recorded i.e. an unmetered gas supply)

Contractor's Registration Number:



158206

Your Landlord Gas Safety Record is over the page

- This is an important document
- You should take a few minutes now to read it
- You may need to refer to this certificate in the future
- Please file it somewhere safe and keep it for a minimum of 2 years

Important safety information for landlords

To help you to better understand your landlord's gas safety record (also known as a landlord certificate or a CP12) we would like to draw your attention to the following key sections.

Appliance Safe

If there is a "NO" in this section please look at the "Details of any defects we found" and "What we've done" sections overleaf. If you are unsure of any comment please contact the landlords team who will be happy to help you.

Indicate YES if Unable to test

If a "YES" has been entered in the column titled "indicate YES If unable to test," then the landlord/agent must obtain additional evidence from any person undertaking subsequent work on the appliance, that the appliance is operating safely.

If we couldn't test appliances

You'll need to get written evidence, and must keep it with this record from anyone that checks and/or carries out any work on it to say it's working safely.

Requested to test

If a "NO" has been entered in the column "Requested to Test" and this relates to a gas appliance at the premise

that does not belong to the current tenant then it may be a breach of the gas safety regulation to rent the property without all gas appliances being checked. The only exception to this is if the appliance has been installed by a gas safe registered engineer and is still under the first year warranty.

NCS or NTCS Not to current standards

AR At Risk. This means that the appliance or installation has one or more recognised faults, and could constitute a danger to life or the property if you or anyone else continues to use it. The appliance/installation has been turned off and you shouldn't use it until work has been carried out to correct the faults identified. It may be an offence to use a gas appliance or installation knowing it is a risk.

ID Immediately Dangerous. This means that your appliance or installation presents an immediate danger to life if you carry on using it or if it's left connected to your gas supply. It's been turned off and should be disconnected for your safety and those around you. Using the isolated installation or equipment before it's been repaired is extremely dangerous. Please do not use it. It is an offence to use a gas appliance or installation knowing it is dangerous.

ECV Emergency control Valve
FSD Flame Supervision Device (also known FFD)
NGES National Gas Emergency Service
PEB Protective Equipotential Bonding
PRV Pressure Relief Valve

ASD


Atmospheric Sensing Device

Additional Emergency control Valve

WAW	WAU	WAL	WAC	TDG	HWS	SLC	OVN	MWH H	SNI	HOB	HGE	GRL	FRE	FRC	FRB	CKR	CIR	GHB	CGE	BBF	BBC	AGA	Key to
Warm Air Unit and Water Heater	Warm Air Unit	Wall Heater	Warm Air Circulator	Gas Tumble Dryer	Single Point Water Heater	Split Level Cooker	Gas Oven	Multipoint Water Heater	Gas Meter, Pipes & Emergency Control Valve	Hob	Electric/Gas Hob	Grill	Gas Fire	Back Circular Fire	Back Boiler Fire	Gas Cooker	Circulator	Central Heating Boiler	Electric /Gas Cooker	Back Boiler Fire	Back Boiler Circular	Aga	Key to Appliance Type Appreviations



Page 2 of 2





Customer Checklist

Your name	Your appointment reference
	1361690388
Your engineer today	Employee number
lanon	56095
Which appliance did we check? Date	Breakdown Annual Service
BLR 821216	Other

Safetu	Summary
_	

For all visits


- 1. Appliance operation is safe
- 2. Appliance flue & ventilation safe
- 3. Functional parts all available
- Electronic Carbon Monoxide alarm manually operated
 - 5. Combustion emissions tested and confirmed as correct

Annual Service Additional checks carried out

- 1. Radiators & visible pipework checked for water leaks & operation
- 2. Appliance electrical safety checked
- 3. Hot water storage cylinder checked (where applicable)
- 4. Magnetic system filter checked
- 5. Appliance / system controls checked (including Hive where fitted)









Parts fitted this visit

Parts ordered

Return visit booked for





Rating Your Current Boiler

Only carried out during annual service

Our engineer has rated your boiler using the SEDBUK scoring system, which is an industry wide measure of how efficient an appliance is.

Your engineer can book an appointment with a local heating adviser. Or if you'd prefer to wait, you can call us on **0800 009 4436****, quoting the employee number on the front of your checklist





Other Ways You Can Save with Us





^{*} We base this on comparing the savings for upgrading a G-rated to an A-rated condensing boiler with a full set of heating controls. The savings assume a gas price of 4.29p/kWh. Source: http://www.energysavingtrust.org.uk/Heating-and-hot-water/Replacing-your-boiler (03/15). Our engineer used a Boiler Efficiency Guide tool, which provides a guide on potential energy savings based on your property type and model of boiler (see SEDBUK/SAP 2005). It does not take into account season variations in the climate which can affect the gas consumption. Older appliances that have not been assessed under the SEDBUK methodology have an 'estimated efficiency' and their efficiency has been determined using Toble 4b of the Government's Standard Assessment Procedure for Energy Rating of Dwellings (EE stands for Efficiency Estimated), you can find the table on the energy saving trust page above. † See the attached chargeable agreement for further details.

**Calls to 0800 numbers are free from landlines and mobiles.

Contract Heating

DOMESTIC ELECTRICAL INSTALLATION CONDITION REPORT (FOR A SINGLE DWELLING) CERTIFICATE ID No.

16320178648-155

Postalf | Service | Repair

Issued in accordance with British Standard 7671-Requirements for Electrical Installations by an Approved Contractor or Conforming Body enrolled with NICEIC, Warwick
House, Houghton Hall Park, Houghton Regis, Dunstable LUS 5ZX.

Records of installation available:	Date of previous inspection:	Estimated age of the electrical installation:		Address:	Occupier		Date(s) on which insp		Purpose for A which this report is required	B. PURPOSE OF THE REPORT		Postcode:			Address:	Client:	A. DETAILS OF THE CLIENT
Records held by: Not Known	Not Known Periodic Installation Certificate No. or previous Not Known Periodic Inspection or Condition Report No: Not Known	lectrical 20 years Evidence of alterations or If yes estimated 5 years additions	Midlothian EH17 75B	17 Nether Craigour	DETAILS OF THE INSTALLATION Occupier Occupier		Date(s) on which inspection and testing were carried out: 15/03/17		Accreditation requirements for renting	HE REPORT		EH17 7SB	Midlothian	Edinburgh	30 Meadow Craigour	Podarama	ECLIENT
	Overall assessment of the (CODE C1) and/or potentially dangerous (CODE C2) installation:	Summary of the condition of the installation No Ves Specify page No(S): N/A continued on additional pages?		Installation is in generally good condition but requires remedial work	General condition of the installation (in terms of electrical safety):	F STIMMARY OF THE CONDITION OF THE INSTALLATION	The inspection and testing have been carried out in accordance with BS 7671, as amended. Cables concealed within trunking and conduits, or cables and conduits concealed under floors, in inacces ble roof spaces and generally within the fabric of the building or underground, have not been visually inspected unless specifically agreed between the client and inspector prior to the inspection.	None	Limitation agreed With: Client Operational limitations including the reasons: see page No. N/A		Intruder alarm system wiring and controls. Smoke detectors points. Central heating wiring and controls. Electrical appliances.Wiring in loft spaces beyond the entrances to hatches.	Agreed Limitations including the reasons, if any, on the inspection and testing:		removed. Zs at all accessible sockets. 20% of all switches, sockets, lights. No Zs at enclosed light fittings.	A visual inspection of all electrical fittings for damage and suitabilty. Bath panels and fixed or built in appliances not	Extent of the electrical installation covered by this report	D. EXTENT OF THE INSTALLATION AND LIMITATIONS ON THE INSPECTION AND TESTING

This report should have been reviewed and confirmed by the registered Qualified Supervisor of the Approved Contractor responsible for issuing it. (See declaration on page 2)

Please see the Notes for recipient at the end of this report

Referring to the attached schedules of inspection and test results, and subject to the limitations at D: F. OBSERVATIONS AND RECOMM There are no items adversely TENDATIONS FOR ACTIONS TO BE TAKEN The following observations and <

Item No affecting electrical safety Code FI 'Further investigation required without delay' AdditionalPages? No Code C3 'Improvement recommended' Code C2 'Potentially dangerous'. Code C1 'Danger present'. One of the following codes, as appropriate, has been allocated to each of the 18 17 16 15 14 13 12 Ħ 10 installation the degree of urgency for remedial action: observations made above to indicate to the person(s) responsible for the Circuit 6 doing sockets and lights Absence of main protective bonding on main water service pipe No No circuit 1 unknown circuit no ring continuity on sockets Consumer Unit in poor condition i.e holesin top and repurposed board Light in ensuite bathroom not ipx4 rated Light damaged in kitchen Cables above consumer unit and in attic left in unsafe condition and no mechanical prot Circuit 7 unkown circuit Absence Socket damaged in kitchen Circuit 4 unknown circuit Switch for rear security light using cpc as line conductor (RECTIFIED, DISCONNECTED) 2x lampholders damaged in rear hall, 2x Lampholders damaged in bed 2 Socket in bed 2 damged (RHS of bed Low insulation values across various circuits RCD for any circuit of main protective bonding on main gas service pipe for socket circuits < Yes [Risk of injury. Immediate remedial action required. Urgent remedial action required Specify page No(s) recommendations for action are made (LHS of sink) circuit 3 Observations required for Items: for items Improvement recommended required for items: Immediate remedial action without delay for items: Further investigation required Urgent remedial action and N/A 11 2,3,8,9,12 1,4-7,10,13-18 C2 Code C2 C2 C2 C2 C2 C2 C2 C2. C2 五 C1 H F₁ E H C2

G. DECLARATION

accurate assessment of the condition of the electrical installation and the limitations on including the observations (see F) and the attached schedules (see H), provide an out the inspection and testing hereby declare that the information on this report, described on page 1 (see C), having excercised reasonable skill and care when carrying installation (as indicated by my/our signatures below), particulars of which are I/We being the person(s) responsible for the inspection and testing of the electrical the inspection and testing (see D).

I/We further declare that in my/our judgement, the overall assessment of the installation in terms of its suitability for continued use is

UNSATISFACTORY

inspected as recommended (see I). (see F) at the time the inspection was carried out, and that it should be further

(CODE C2) conditions have been identified, or that Further investigation without delay (F1) is An 'Unsatisfactory' assessment indicates that dangerous (CODE C1) and/or potentially dangerous

INSPECTION, TESTING AND ASSESSMENT BY:

Signature

BEN MILLER

Date: Position: Name: (CAPITALS) Electrician 15/03/17

REPORT REVIEWED AND CONFIRMED BY:

Signature

Digitally signed by Ian McImtosh
DN: cn=lain McIntosh, o=Contract Heating Ltd.,
ou=Electrical,
email=lammcintosh@contractheating co.u.k, c=CB
Date: 2017.03.20 11:24:49 Z

Name: (CAPITALS) (Registered Qualified Supervisor for the Approved Contractor at J) lan McIntosh

H. SCHEDULES AND ADDITIONAL PAGES

Schedule of Inspections: Page(s) No 4.5,6

additional source(s) Additional pages, including data sheets for

Page No(s) N/A

Schedule of Test Results for the installation: Schedule of Circuit Details for the installation

Page No(s) 7

Page No(s) 7

accompanied by all the schedules and additional pages identified above The pages identified are an essential part of this report. The report is valid only if

ification codes' at the end of this report se see the 'Guidance for recipients on the Please see end of this document for guidance regarding the Classification codes

DOMESTIC ELECTRICAL	INSTALLATIO	DOMESTIC ELECTRICAL INSTALLATION CONDITION REPORT (FOR A SINGLE DWELLING) CENTILICATE ID NO.	A LILLING) CLEAN CO.	1000
ISPECTION	J. DETAILS OF I	J. DETAILS OF NICEIC APPROVED CONTRACTOR		
mend that this installation is further inspected and tested after				
of not more than:	Trading title:	Contract Heating Ltd.		
(Enter interval in terms of years or months, as appropriate)	Address:	2B Bankhead Crossway South	Telephone number: 0131 458 3377	
at any items at F which have been attributed a Classification		Edinburgh	Email address: electrical@contractheating.co.uk	tractheating.co.uk
nger present) are remedied immediately and that any items been attributed a code C2 (potentially dangerous) or require		Midlothian	NICEIC Enrolment number: 031779	
rgency. Items which have been attributed a Classification code	Postcode:	EH11 4EX	Branch number: NA	
simply of soon as practicable (see E)				

NEXT INSPECTION	J. DETAILS OF N	J. DETAILS OF NICEIC APPROVED CONTRACTOR	ACTOR	
/We recommend that this installation is further inspected and tested after in interval of not more than:	Trading title:	Contract Heating Ltd.		
Years	Hadring diese.			
(Enter interval in terms of years or months, as appropriate)	Address:	2B Bankhead Crossway South	y South	Telephone number: 0131 458 3377
provided that any items at F which have been attributed a Classification		Edinburgh		Emailaddress: electrical@contractheating.co.uk
ode C1 (danger present) are remedied immediately and that any items which have been attributed a code C2 (potentially dangerous) or require		Midlothian	NICE	NICEIC Enrolment number: 031779
urther investigation are remedied or investigated respectively as a natter of urgency. Items which have been attributed a Classification code	Postcode:	EH11 4EX		Branch number: NA
3 should be improved as soon as practicable (see F).		2		
. SUPPLY CHARACTERISTICS AND EARTHING ARRANGEMENTS	Tick boxes or enter	Tick boxes or enter details as appropriate		Characteristics of primary supply
			Nature of supply parameters	Oscilon sain desire(a)
System type(s) Number and type of live conductors			A COLUMN TO A COLU	BS(EN) 1361
	state)	Nominal voltage(s)	(1) 230 V Uo(1)	V Type 11a
1-phase 1-phase		Nominal		Rated current 60 A
<		frequency,f(1)	(1) 50 Hz sources	
2-phase 3-phase (3-wire) (4-wire)		Prospective fault current, lpf(2)(3)	0.661 kA	Notes : Capacity 33 kA (3) by enquiry for by measurement Confirmation of
3-phase		External earth fault loop impedance. Ze(3)(4)	0.35	Leafue
. PARTICULARS OF INSTALLATION AT THE ORIGIN Tick boxes or enter details as appropriate	enter details as appro	opriate		
Means of earthing		Deta	Details of installation earth electrode (where applicable)	where applicable)
Distributor's Type: (eg rod(s), tapes facility: etc)	NA	Location: NA		
Installation Electrode: Electrode resistance, \mathbb{R}_{t} NA	50	Method of measurement: NA		
Main switch/Switch-Fuse/Circuit-Breaker/RCD			Earthing and protective bonding conductors	nding conductors
Type Voltage Voltage SS(EN) 60947 rating 240 V			Main protective handing conductors	Bonding of extraneous-conductive-parts
No of Rated Rated current, in 100 A	Cor	Conductor	Conductor	Water installation Lighting Other (Speci
Primary supply RCD operating	3	material Copper	material	pipes protection
aterial) Copper cur	Cor	Conductor	Conductor	Oil installation pipes Struc
Primary supply Rated time conductors (csa) 25 frr delay* ms		csa 16	CSa	frri steel
RCD operating time {at اردیاناً ms	Connection continuity verified	Connection uity verified	Connection/continuity verified	Gas installation proes
* (applicable only where an RCD is suitable and is used as a main circuit-breaker)	7)			

	IESTIC ELECTRICAL INSTALLATION CONDITION REPORT (FOR A SINGLE DWELLING) CERTIFICATE ID	
	\equiv	
	\subseteq	
	\overline{C}	
	Ξ	
ľ	$\overline{\bigcirc}$	
ı	7	
ı	=	
	S	
ŀ	\triangleright	
	-	
l	\equiv	
ı	0	
l	2	
l	0	
ı	Z	
l	\subseteq	
	\equiv	
ı	\geq	
ı	D	
ı	E	
ı	유	
ŀ	$\widetilde{\neg}$	
	(FO	
ı	8	
	\triangleright	
ı	S	
ı	NGLE DV	
١		
ı		
۱	Š	
ı		
۱		
Ì	Z	
ı	0	
ł	IG) CERTIFICATE ID	
I	뜄	
ł	≓	
ı	ä	
۱	A	
ı	mi	
	D	
ı	Z	
	P	
	16	
	5320	
	01	
	16320178648-155	
	96	
	18	
	i.	
	55	

	00	3.7	3.6	in		ω	3.2	3,1	3.0		7	2.1	2.0	1.6	1.5	1.4	1.3	1.2	1.1	1.0	Item	SCHE
Where inadequacies in distributor's equipment are encountered, it is	Provision of earthing and bonding labels at all appropriate locations	Accessibility and condition of other protective bonding connections	Accessibility and condition of main protective bonding conductor connections	Confirmation of adequate main protective bonding conductor sizes	Accessibilty and condition of earthing conductor at Main Earthing Terminal (MET)	Confirmation of adequate earthing conductor size	Presence and condition of earth electrode connection	Presence and condition of distributor's earthing arrangement	Earthing and bonding arrangements	operates in parallel with the public supply	Supply Adopting arrangements where a generating set	Adequate arrangements where a generating set	Presence of adequate arrangements for other sources	Means of main isolation (where present)	Metering equipment	Meter tails - Distributor/Consumer	Distributor's earthing arrangement	Service head	Service cable	Condition/adequacy of distributor's/supply intake equipment	Description	SCHEDULE OF INSPECTIONS
red, it is		<		<	<	<		<					ırces		<	<	<	<	<	equip		
	C2		Ω				N/A			N/A	N/A		(microgenerators etc)	N/A						ment	Outcome* Location reference	
4.17	4.16		4.15	4.14	4.13	4.12	į	2	4.10	4.9	4.00	4.7	4.6	4.5	4.4	4.3	4.2		4.1	4.0	Item	
7 Protection against mechanical damage where	5 Single-pole switching or protective devices in the line conductors only	thermal damage, arcing or overheating)	correct type and rating (no signs of unacceptable	Presence of other required labelling (please specify)	Presence of replacement next inspection recommendation label.	Presence of alternative supply warning notice at or near consumer unit	warning notice at or near consumer unit			Correct identification of circuits and protective devices	Operation of circuit-breakers and RCDs to prove disconnection (functional check)	Operation of main switch (functional check)	Presence of linked main switch	Enclosure not damaged/detenorated so as to impair safety	Condition of enclosure(s) in terms of fire rating	Condition of enclosure(s) in terms of it rating	Security of fixing	consumer unit	Adequacy of working space or access to	Consumer unit(s)	Description	
	•	<			<						<	<						. <			0	
				N/A		N/A	CZ	N/A		C2				Ω	2	3 6	3				Outcome* Location reference	

' 💞 Indicates Acceptable condition *All boxes must be completed.

'LIM' indicates a Limitation

Improvement recommended state C3 Unacceptable condition state C1 or C2 'N/A' indicates Not applicable

> (to determine whether danger or potential danger exists) Further investigation required state F/I

C1, C2, C3 and F1 coded items to be recorded in Section F of the report. Provide additional comment where appropriate on attached numbered sheets.

Outcome

Outcome* Location reference Item N/A	Protection splints electronarganetic effects where calcinomental protection and protection applies electronarganetic effects where calcinomental protection applies electronarganetic effects where calcinomental protection applies electronarganetic effects where calcinomental protection applies electronary calcinomental protection includes calcinomental calcinomen	Outcome Provide additional comment where appropriate on attached numbered sheets	e F/I Outcome Provide additional comment where	Further investigation required state F/I	'N/A' indicates Not applicable	All boxes must be completed. 'N/A' indicat	All boxes mu
Outcome* location reference Item Description	Description Description Description Doutcome* Location reference N/A Protection against electromagnetic effects where cables enter metallic consume willy enclosure cables enter metallic consume will enclosure cables enter metallic consumer will enclose connections to bubars are correctly including connections to bubars are correctly located in terminals and are tight and secure light and secure located in terminals and are tight and secure located in terminals and are tight and secure by enclosure in condition of insulation of insulation of inve parts Cables correctly supported throughout their run	ay not have been provided with RC	+ Note: Older installations designed prior to BS 7671:2008 ma			and limitations)	
Outcome* Location reference Item Description	Description Distance of a payment electromagnetic effects where cables enter metallic consumer unit/enclosure RCDs provided for fault protection-includes RCDs provided for additional protections to bushars are correctly including connections to bushars are correctly supported throughout their run RCDs provided for additional protection for an are tight and secure Final Circuits Cables correctly supported throughout their run RCDs protective devices protected by enclosure in confinmation of fine integrity of conduits and trunking (including confirmation of fine integrity of conduits and trunking systems) Adequately protective devices type and nature of installation Adequate of protective devices to the type and nature of installation and external influences Co-ordination between conductors and overload RCDs partitions, adequately protected against damage Extra Cables against cannels Adequately winds systems) Adequately protective devices above ceilings, in walls / partitions, adequately protected against damage Enclosure and adequately protection and external influences Connective devices Connective dev	C2			LIM	ed in prescribed zones (see Section D.	
Outcome* Location reference Item Description	Description Description Dutcome* Location reference Item Description Protection against electromagnetic effects where cables enter metallic consumer unit/lendosure cables provided for additional protection-includes C2 C2 C2 C2 C3 C3 C3 C3				ls / partitions, adequately pro	istalled under floors, above ceilings, in wal	
Outcome* Location reference N/A	HEDULE OF INSPECTIONS Description Description Description Protection against electromagnetic effects where cables enter metallic consumer unit/enclosure Cables enter metallic consumer unit/enclosure CRCDs provided for fault protection-includes RCDs provided for fault protection-includes RCDs provided for fault protection-includes RCDs provided for fault protection-includes CC2 CC2 CC3 RCBOS		of entry to		C2	/stem(s) appropriate for the type and f the installation and external influences	
Outcome* Location reference N/A	HEDULE OF INSPECTIONS Dutcome* Location reference Item Description Protection against electromagnetic effects where cables enter metallic consumer unit/enclosure N/A Section provided for fault protection-includes C2 Section D. RCBOS RCBOS provided for fault protection-includes C2 Section D. RCBOS Confirmation of indication that SPD is functional N/A For mobilifying connections to busbars are correctly located in terminals and are tight and secure Final Circuits E1 L1M Cables correctly supported throughout their run N/A Secure S.11 Provision of and protection of invitation of invitatio				\$	ation between conductors and overload re devices	
Outcome* Location reference Item Description Item Description Incorporation Incorporat	HEDULE OF INSPECTIONS Dutcome* Location reference Item Description Protection against electromagnetic effects where cables enter metallic consumer unit/enclosure RCDs provided for fault protection-includes RCDs provided for fault protection-includes RCDs provided for additional protection-includes RCDs provided for addition of including that StD is functional N/A For ables including connections to busbars are correctly supported throughout their run N/A FI Cables correctly supported throughout their run N/A Solution of insulation of live parts Condition of insulation of live parts Condition of insulation of live parts Non-sheathed cables protected by enclosure in cables conduit, ducting or trunking (including connections) Confirmation of the integrity of conduit and trunking systems) Adequacy of cables for current-carrying capacity with regard to the type and nature of installation Adequacy of protection Connection Co	€	of a conductor visible		C2	and adequacy of circuit protective	
Outcome* Location reference N/A	Protection against electromagnetic effects where cables enter metallic consumer unit/enclosure Protection against electromagnetic effects where cables enter metallic consumer unit/enclosure Protection against electromagnetic effects where cables enter metallic consumer unit/enclosure Protection against electromagnetic effects where cables enter metallic consumer unit/enclosure Protection by RCDs provided for fault protection-includes RCDs provided for fault protection-includes RCDs provided for additional protection-includes RCDs provided for addition of indication that SLL conductor connections, including connections to busbars are correctly located in terminals and are tight and secure Final Circuits Including connections to busbars are correctly conductors Cables correctly supported throughout their run RV/A SIL Provision of and protection of insulation of five parts Cables protected by enclosure in Cables correctly supported throughout their run RV/A SIL Provision of solvention of insulation of five parts Cables segre confirmation of the integrity of conduction of conducting confirmation of the integrity of conduction of conducting confirmation of the integrity of conducting confirmation of the part of installation CC2 SIL Provision of solvention of insulation of invention of invention of insulation of invention of inventio		soundly made and under no		C2	y of protective devices type and rated or fault protection	
Outcome* Location reference N/A	Description Description Dutcome* Location reference Item Description Dutcome* Dutcome	ling indicated in Section D of t	Termination	5.16		ard to the type and nature of mistanation	With re
Outcome* location reference Item Description Outcome*	Protection against electromagnetic effects where C2	N/A		5.19	C2	y of cables for current-carrying capacity	5.5 Adequ
Outcome* Location reference ftem Description	Protection against electromagnetic effects where cables enter metallic consumer unit/enclosure RCBs provided for fault protection-includes RCBs (C2) RCBs provided for fault protection-includes C2 RCBs provided for additional protection-includes C3 RCBs provided for additional protection-includes C4 Confirmation that ALL conductor connections, including connections to busbars are correctly located in terminals and are tight and secure Final Circuits Cables correctly supported throughout their run C5 Condition of insulation of live parts Condition of insulation of live parts Cables protected by enclosure in C4 LIM Outcome* Item Description Outcome* Incorporating earthed armour or sheath, or inscalled within earthed armour or sheath, or inscalled within earthed within earthed armour or sheath, or inscalled within earthed	□ N/A	Cables segre	5.14		ducting or trunking (including tion of the integrity of conduit and	condu
Outcome* Location reference N/A	Protection against electromagnetic effects where cables entermetallic consumer unit/enclosure conference cables entermetallic consumer unit/enclosure cables entermetallic consumer unit/enclosure cables entermetallic consumer unit/enclosure cables entermetallic consumer unit/enclosure cables installed within earthed writing system, or otherwise protected against mechanical damage by nails, screws and the like (see section D. Extent and limitations) Confirmation of indication that SPD is functional cables functional protection by RCD not exceeding 30 mA Tor all socket-outlets of rating 20 A or less cables installed in walls or partitions at a depth of less than 50mm Final Circuits Gables correctly supported throughout their run cables installed in walls or partitions at a depth of less than 50mm Final Circuits Gables correctly supported throughout their run cables installed in walls or partitions containing metal parts regardless of depth cables installed in walls or partitions and part in cables installed in walls or partitions containing metal parts regardless of depth cables correctly supported throughout their run cables installed in walls or partitions and part in cables installed in walls or partitions and part in cables installed in walls or partitions and part in cables installed in walls or partitions and part in cables installed in walls or partitions and part in cables installed in walls or partitions and part in cables in cables in cables in cables in cables in cable	N/A		5.13		athed cables protected by enclosure in	5.4 Non-sh
Outcome* Location reference N/A	Protection against electromagnetic effects where N/A	C2	and protecti	5.11		orrectly supported throughout their run	
Outcome* Location reference N/A	Description Descr	N/A	containin		FIL	ition of conductors	
Outcome* Location reference Item Description N/A	Description Descr		for cables installed in walls / partitions			uits	5.0 Final C
Outcome* Location reference Item Description N/A	Description Description Outcome* Location reference N/A Protection against electromagnetic effects where cables enter metallic consumer unit/enclosure RCDs provided for fault protection-includes RCBos RCBos RCBOs RCBOs Confirmation of indication that SPD is functional Confirmation that ALL conductor connections, Outcome* Description Outcome* N/A Item Description Outcome* Item Description Outcome* Incorporating earthed armour or sheath, or installed within earthed wiring system, or otherwise protected against mechanical damage by nails, screws and the like (see Section D. Extent and limitations) N/A S.11 Provision of additional protection by RCD not exceeding 30 mA For all socket-outlets of rating 20 A or less Confirmation that ALL conductor connections, Outcome* Outcome* Outcome* Item Description Incorporating earthed armour or sheath, or installed within earthed wiring system, or otherwise protected against mechanical damage by nails, screws and the like (see Section D. Extent and limitations) N/A For all socket-outlets of rating 20 A or less Outcome* Outcome*		ls or partitions at a			connections to busbars are correctly terminals and are tight and secure	includi
Outcome* Location reference Item Description N/A incorporating earthed armour or sheath, or installed within earthed wiring system, or otherwise protected against mechanical damage by nails, screws and the like (see Section D. Extent and limitations) C2 C2 5.11 Provision of additional protection by RCD not exceeding 30 mA for all socket-outlets of rating 20 A or less N/A	Description Outcome* Location reference Protection against electromagnetic effects where cables enter metallic consumer unit/enclosure RCDs provided for fault protection-includes RCDs provided for additional protection by RCD not exceeding 30 mA RCDs provided for additional protection by RCD not exceeding 30 mA For all socket-outlets of rating 20 A or less CC2 CC2 CC3 CC3 CC3 CC3 CC3 C	N/A	for mobile equipment not exceeding a rating of 32 A rating for use outdoors		S	tion that ALL conductor connections,	.22 Confir
Outcome* Location reference Item Description N/A incorporating earthed armour or sheath, or installed within earthed wiring system, or otherwise protected against mechanical damage by nails, screws and the like (see Section D. Extent and limitations) C2 C3 C4 S5.11 Provision of additional protection by RCD not exceeding 30 mA	Description Outcome* Location reference Protection against electromagnetic effects where cables enter metallic consumer unit/enclosure RCDs provided for fault protection-includes RCDs provided for additional protection-includes RCDs provided for additional protection-includes C2 RCDs provided for additional protection-includes C3 C4 C5 C5 C6 C6 C7 C6 C7 C7 C7 C8 C8 C9 C9 C9 C9 C9 C9 C9 C9		for all socket-outlets of rating 20 A or less		N/A	tion of indication that SPD is functional	4.21 Confirm
Outcome* Location reference Item Description N/A incorporating earthed armour or sheath, or installed within earthed wiring system, or otherwise protected against mechanical damage by nails, screws and the like (see Section D. Extent and limitations)	Description Outcome* Location reference Protection against electromagnetic effects where cables enter metallic consumer unit/enclosure RCDs provided for fault protection-includes Outcome* Location reference N/A Outcome* Location reference N/A Outcome* Location reference N/A Outcome* Countered armour or sheath, or installed within earthed armour or sheath, or otherwise protected against mechanical damage by nails, screws and the like (see Section D. Extent and limitations) N/A RCBOS	ing 30 mA	Provision of	5.11	C2	vided for additional protection-includes	4.20 RCDs p
Outcome* Location reference Item Description N/A incorporating earthed armour or sheath, or installed within earthed wiring system, or otherwise protected against mechanical	Protection against electromagnetic effects where acables enter metallic consumer unit/enclosure Outcome* Location reference ltem Description Outcome* location reference ltem Description ltem ltem ltem ltem ltem ltem ltem ltem	N/A	damage by nails, screws and the like (see Section D. Extent and limitations)		C2	vided for fault protection-includes	4.19 RCDs p RCBOs
Outcome* Location reference Item Description Outcome*	REDULE OF INSPECTIONS Outcome* Location reference Item Description Outcome*		 incorporating earthed armour or sheath, or installed within earthed wiring system, or otherwise protected against mechanical 		N/A	n against electromagnetic effects where ter metallic consumer unit/enclosure	1,18 Protect
	CHEDULE OF INSPECTIONS					on	tem Descrip

Unacceptable condition state C1 or C2 Improvement recommended state C3

(to determine whether danger or potential danger exists)

C1, C2, C3 and F1 coded items to be recorded in Section F of the report.

' ✓' Indicates Acceptable condition 'LIM' indicates a Limitation

m	ı		٠
m	r	_	
ш	£	J	י ני
	3	٠.	ď
	ţ	۸	4
и.		Ū	١
и.	ı	•	-
	ť	_	٦
	3	-	1
ш	١	-	4
	-	_	٠
	1	S	٩
11	3	~	2
	•	۰	7
ш		ī	L
и.		٠	2
и.	1	٦	٥
W.	٩	4	۳
ш		1	
		_	ď
	ä		
ш	Ŋ	J	
11	1	1	۲
n.	1	_	

Ξ •	}		7.5	1.	7	7.3	1.2		7.0		6.3						5.2		1.1		0.0	5.20	5.19	tem	£ S
√ Indicates Acceptable condition I'M' indicates a Limitation I'M' Indicates a Limitation I'M' I'M'	All boxes must be completed.		Security of fixing	influences	Cuitability for the environment of	Enclosure not damaged/deteriorated so as to impair safety	hazard	rating	Current-using equipment (Permanently connected) Condition of equipment in terms of IP	 where live parts cannot be isolated by the operation of a single device 	For isolation only warning label(s) posted in situations	durable marking(s)	 clearly identified by position and/or 	from equipment being controlled where	acceptable location-state if lo	 capable of being secured in the OFF position where appropriate 	For isolation and switching for mechanical maintenance only	 correct operation verified 	 presence and condition of appropriate 	switching)	Isolation and switching (isolation, switching off for mechanical maintenance and functional	Single-pole devices for switching or protection in line conductors only	Adequacy of working space / accessibility to equipment	Description	SCHEDULE OF INSPECTIONS
Unacceptab	'N/A' indicat		- A.S.	and external	and external	orated so as to	d III d		Permanently c	solated by the	tuations		and/or	olled where	ocal or remote	the OFF	mechanical main		propriate		olation, switch	ig or	ccessibility to		
le condition nt recomme	N/A' indicates Not applicable		<		[()	3	onnected]				tenance on				ing off for	•	S	Outc	
Unacceptable condition state C1 or C2	icable			R		Ω				N/A		N/A		N/A		N/A	ılγ				mechanical m			Outcome* Location reference	
(to determine whether danger or potential danger exists)	Further investigation required state F/I	4.1	9.0		8.7		8.6	8.5	8,4	В	8.2				8.1	8,0						7.7	7.6	reference Item	
	ate F/I											fo Zv	•				0.20	b 20	₽ . [6	Ξ					
Provide additional comment where appropriate on attached numbered sneets C1, C2, C3 and F1 coded items to be recorded in Section F of the report.	Outcome	present, if any. (Record the results of particular inspection applied seperately)	Other special installations of locations	particular zone	Suitability of equipment for installation in a	for installed location in terms of IP rating	Suitability of equipment for external influences	Low voltage (e.g. 230 volts) socket-outlets	Presence of supplementary bonding conductors unless not required by BS 7671:2008	Shaver sockets comply with BS EN 61558-2-3 or BS 3535	Where used as a protective measure, requirements for SELV or PELV are met	for low voltage circuits passing through Zone 1 and Zone 2 not serving the location	location	for low voltage circuits serving the	Additional protection by RCD not exceeding 30 mA	Location(s) containing a bath or shower	no signs of overheating to conductors/terminations	no signs of overheating to surrounding building fabric	use of 'fire rated fittings, insulation displacement box or similar	installed to minimise build-up of heat by	correct type of lamps fitted	inspected. (Seperate page) Renessed luminaires (downlighters)	Cable entry holes in ceiling above luminaires, sized or sealed so as to restrict the spread of fire. List number and location of luminaires.	Description	
re approp be record			01673	¥ 7]	<		\	<						mA									o	
riate on ai		N/A								N/A	N/A	Ω	2				N/A	N/A	N/A		N/A	N/A		Outcome*	10
tached numbered sneets.																								Location reference	THE RESIDENCE

'LIM' indicates a Limitation

Improvement recommended state C3

DOMESTIC ELECTRICAL INSTALLATION CONDITION REPORT (FOR A SINGLE DWELLING) CIRCUIT SCHEDULES

		ulated	Mineral insulated	Thermosetting/SWA	Thermoplastic/SWA		Thermoplastic cables		Thermoplastic cables		Thermoplastic cables	Thermop	Thermoplastic cables	Thermoplastic	
state)	O(Other please state)		ı	G	п		m		o		С		В	>	
					CODES FOR TYPE OF WIRING	CODES									
	RCD	Earth fault loop impedance	Earth fault l		Earth electrode resistance			Continuity	Cor			insulation resistance	00	Multi- functional 101397328	-h ==
					Č		(china is	20150111	DESIGNATION OF CONSUMER WINES	4	bers used	serial nun	S Test Instrument serial numbers used	TEST INSTRUMENTS	
	0.661	Prospective fault current at consumer unit(s)	ult current at	Prospective fa	AG	D	or unit(s)	f consum.	elenation						-
														00	18
														7	17
														6	16
														(5)	15
														4 Spare	14
														3 Spare	13
														2 Spare	12
														1 Spare	11
	200.00 0.00	20	0.53			6	50	60898	1.0 0.4	1.0		A C			10
	0.00 0.00 🗆 1.06	0	0.71			6	σ.	60898	1.0 0.4	1.0		A C			9
	0.00 0.00 🗆 0.44	0	0.09			6	σ.	60898	1.5 0.4	2.5		A C		Boiler	00
	200.00 0.00 🗆 0.00	20	0.00			16 6	σ.	60898	1.5 0.4	2.5		A C		Unknown	7
	0.00 0.00 🗆 0.77	0	0.42			16 6	σ.	60898	1.5 0.4	2.5		A C	ghts	Sockets and Lights	σ
														Spare	ы
	0.15 0.00 🗌 0.00	0	0.00			32 6	B	60898	1.5 0.4	2.5		A C		Unknown	4
	0.00 0.00 🗌 1.28	0	0.93			32 6	В	60898	1.5 0.4	2.5		A C		Sockets	ω
	200.00 0.00 0.55	20	0.20			32 6	00	60898	2.5 0.4	6.0 2	ь	A C		Cooker	Ν
	200.00 0.00 🗆 0.00	20	0.00			40 6	В	60898	4.0 5.0	10.0 4	-	A C		Unknown	۲
Operating times 18. at 1 at 5 delta n delta n ms ms	messured Zime / Neutral loop Earth / Earth / E	Line / Line / Line Line Mohm Mohm Mohm Mohm Mohm Mohm Mohm Mohm	All circuits (At east one circuit to be (R1+R2)	g final circuits only assured end to end) [Ref (Neutral)] [Cpc]	1109Tilus Dinistrand C 1707 S8 W bellimad 25, xsh	Short circuit	[уре Мо	BS (EN)	by 85 7671	Live c	ber of points ed rence method (see	(1787 28 to the widow 9 of Wiring (See	Circuit designation Circuit designation To be completed only where this consumer unit is remote from the origin of the installation Record details of the circuit supplying this consumer unit in the bold box.		Circuit Mumber
RCD	loq	Insulation resistance		Circuit impedances	9		ect	Overc	bəttimra	Circuit conductors:	VIÐS	edde		CIRCUIT DETAILS	0

GUIDANCE FOR RECIPIENTS ON THE CLASSIFICATION CODES

Only one Classification code should have been given for each recorded observation

Classifiction code C1 (Danger present)

Where an observation has been given a Classification code C1, the safety of those using the installtion is at risk and immediate remedial action is required.

The person responsible for the maintenance of the installation is advised to take action without delayto remedy the observed deficiency in the installtion, or take other appropriate action (such as switching off and isolating the affected part(s) of the installtion) to remove the danger. The NICEIC Approved Contractor issuing this report will be able to provide further advice.

Classifiction code C2 (Potentially dangerous)

Classification code C2 indicates that, whilst those using the installtion may not be at immediate risk, URGENT REMEDIAL ACTION IS REQUIRED TO REMOVE POTENTIAL DANGER. The NICEIC Approved Contractor issuing this report will be able to provide further advice.

Classifiction code C3 (Improvement recommended)

Where an observation has been given a Classification code C3, the inspection and/or testing has revealed a non-compliance with the current safety standard which, whilst not presenting immediate or potential danger, would result in a significant safety improvement if remedied. Careful consideration should be given to the safety benefits of improving these aspects of the installation. The NICEIC Approved Contractor issuing this report will be able to provide further advice.

It is important to note that the recommendation given at Section 1 of this report (Next Inspection) for the maximum interval until the next inspection is conditional upon all items which have been given a classification code C1 and code C2 being remedied immediately and as a matter of urgency respectively.

It would not be reasonable for the inspector to indicate that the installation is in satisfactory condition if any observation in this report has been given a code C1 or code C2 classification or requires further investigation.

Requires further investigation

It should usually be possible for the inspector to attribute a Classification code to each observation without indicating a need for further investigation.

However where a "Yes" has been entered against an observation in the "Further investigation required" column of section F, the inspector considers that further investigation of that observation is likely to revela danger or potential danger that, due to the agreed extent or limitations of the inspection and/or testing, could not be fully identified at the time.

It would not be appropriate for the inspector to indicate that the installation is in a satisfactory condition if there is reasonable doubt as to whether danger or potential danger exists.

If the inspector has indicated that an observation requires further investigation, the person ordering this report advised to arrange for the NICEIC Approved Contractor issuing the report (or another competent person) to undertake further examination of that aspect of the installation as a matter of urgency to determine whether or not danger or potential danger exists.

Further information

Further information on the application of Classification codes, primarily aimed at inspectors but of possible interest to persons ordering condition reports, can be found in the Electrical Safety Council's Best Practice Guide entitled Electrical installation condition reporting: Classification Codes for domestic and similar electrical installations. The guide can be viewed or downloaded free of charge from www.esc.org.uk

NOTES FOR RECIPIENT

THIS DOMESTIC ELECTRICAL INSTALLATION CONDITION REPORT IS AN IMPORTANT AND VALUABLE DOCUMENT WHICH SHOULD BE RETAINED FOR FUTURE REFERENCE

The purpose of periodic inspection is to determine, so far as is reasonably practicable, whether an electrical installation is in satisfactory condition for continued service (see Section E and G). This report provides an assessment of the condition of the electrical installation identified overleaf at the time it was inspected and tested, taking into account the stated extent of the installation and the limitations of the inspection and testing.

The report identifies any damage, deterioration, defects and/or conditions found by the inspector which may give rise to danger (see section F), together with any items for which improvement is recommended.

If you were the person ordering this report, but not the user of the installation, you should pass this report, or a full copy of it including these notes, the schedules and additional pages (if any), immediately to the user.

This report should be retained in a safe place and shown to any person inspecting or undertaking further work on the electrical installation in the future. If you later vacate the property, this report will provide the new user with an assessment of the condition of the electrical installation at the time the periodic inspection was carried out.

Where the installation incorporates residual current devices (RCDs), there should be a notice at or near the consumer unit stating that they should be tested quarterly. FOR SAFETY REASONS, IT IS IMPORTANT THAT YOU CARRY OUT THE TEST REGUARLY.

For safety reasons, the electrical installation should be re-inspected at appropriate intervals by a skilled person or persons competent in such work. The recommended date by which the next inspection should be carried out is stated in section I of this report. There should also be a notice at or near the consumer unit indicating when the next inspection of the installation is due. NICEIC* recommends that you engage the services of an Approved Contractor for the inspection.

This report has been issued in accordance with the national standard for the safety of electrical installations, British Standard 7671 (as amended) - Requirements for Electrical Installations

Only an NICEIC Approved Contractor or Conforming Body is authorised to issue this NICEIC Domestic Electrical Installation Condition Report form.

This report consists of at least nine numbered pages. Additional numbered pages may have been provided to permit further relevant information relating to the installation to be recorded. For installations having more than one consumer unit or more circuits than can be recorded on Page 7, one or more additional Schedules of Circuit Detials and Test Resuts for the installation should form part of the report. This report is invalid if any of the pages identified in Section H are missing.

This report form is intended to be issued only for the purpose of reporting on the condition of an existing domestic electrical installation. The report should identify, so far as is reasonably practicable and having regard to the extent and limitations recorded in Section D, any damage, deterioration, defects, dangerous conditions and any non-compliances with the requirements of the national standard for safety of electrical installations which may give rise to danger, together with any items for which improvement is recommended.

The report should not have been issued to certify that new electrical installation work complies with the requirements of the national safety standard. An 'Electrical Installation Certificate' a

"Domestic Electrical Installation Certificate" or a "Minor Electrical Installation Works Certificate" (as appropriate) should be issued for the certification of new installation work.

Section D (Extent and limitations) should identify fully the extent of the installation covered by this report and any limitations on the inspection and testing. The inspector should have agreed these aspects with the person ordering the report and with other interested parties (licensing authority, insurance company, mortgage provider and the like) before the inspection was carried out.

Some operational limitations may have been encountered during the inspection such as inability to gain access to parts of the installation or to an item of equipment. The inspector should have noted any such limitations in Section D.

It should be noted that the greater the limitations applying to a report, the less it's value from the safety aspect.

A declaration of the overall condition of the installation should have been given by the inspector in Section G of the report. The declaration must reflect the statement given in Section E, which summarises the observations and recommendations made in Section F. Where one or more observations have been made in Section F, the classification code given to each by the inspector indicates the degree of urgency with which remedial action needs to be taken to restore the installation to a safe working condition.

Where the inspector has indicated an observation or code C1 (danger present) the safety of those using the installation is at risk, and it is recommended that a skilled person competent in electrical installation work undertakes the necessary remedial work immediately.

Where the inspector has indicated an observation or code C2 (potentially dangerous) the safety of those using the installation is at risk, and it is recommended that a skilled person competent in electrical installation work undertakes the necessary remedial work as a matter of urgency.


Where the inspector has indicated further investigation F1, the investigation should be carried out without delay to determine whether danger or potential danger exists. For further guidance on the Classification codes, please see page 8.

Where inadequacies in the electricity distributor's or supplier's equipment have been observed (Section 1 of the Schedule of Inspections), the person ordering the inspection should inform the distributor and/or supplier as appropriate.

Should the person ordering this report have reason to believe that it does not reasonably reflect the condition of the electrical installation reported on, that the person should in the first instance raise the specific concerns in writing with the NICEIC Approved Contractor. If the concerns remain unresolved, the person ordering this report may make a formal complaint to NICEIC, for which purpose a complaint form is available on request.

The complaints procedure offered by NICEIC is subject to certain terms and conditions, full details of which re available upon application. NICEIC does not investigate complaints relating to the operational performance of electrical installations (such as lighting levels), or to contractural or commercial issues (such as time or cost).

For further information about electrical safety and how NICEIC can help you, visit www.niceic.com



ATION Certificate No. 243201773324-333 ICAL INSTALLATION

Install | Service | Repair

Issued in accordance with British Standard 7671-Requirements for Electrical Installations by an Approved Contractor or Conforming Body enrolled with NICEIC, Warwick Hall Park, Houghton Regis, Dunstable LU5 5ZX

To be used only for minor electrical work which does not include the provision of a new circuit

PART 1: DETAILS OF THE MINOR WORKS			Details of depa	rtures, if any, from	BS 7671 (as ar	nmended):	
lient: Podarama							
ate minor works completed: 24-Mar-17							
escription of the minor works:			Location/addre	ess of the minor we	orks:		
eplaced 2x sockets for RCD sockets at front and back of p	roperty		17	Nether Craigour			
, placea 2.1.22.11.12				Edinburgh			
				Midlothian			
				EH17 7SB			
PART 2: DETAILS OF THE MODIFIED CIRCUIT						341	
ystem type and earthing arrangements:	TN-C-S	TN	-S ☑ π	TN-C] п 🗌		
otective measures against electric shock:		ADS					
vercurrent protective device for modified circuit:	BS(EN)	60898		Type B	Ra	iting 16	Α
esidual current device (if applicable):	BS(EN)			Туре		I _{An}	mA
Details of wiring system used to		Refer	ence ethod A	csa of lives 2	5 mm²	csa of cpc 1.5	s mm
nodify the circuit: Where the measure for protection against electric shock	is ADS, insert max		0.4	Maxir	num Zs permitt	ed by BS 7671	Ω
isconnection time permitted by BS 7671:							
omments, if any, on exisiting installation, including adec	quacy of earthing a	and bondir	ng arrangemen	ts (see Regulation	132.16):		
PART 3: INSPECTION AND TESTING OF THE MODI	IEIED CIRCUIT A	A LOS DO DE LA P					
	IFIED CIRCOII A	ND RELA	TED PARTS				
			Insulation res		wor or lowest value	ie as appropriate)	
Confirmation that necessary inspections have been und		✓ (∕)	Insulation res	circuit, record the lov			200 M
Confirmation that necessary inspections have been undecended for the adequacy of earthing		✓ (/) ✓ (/)	Insulation resi (In a polyphase Line	circuit, record the lov /Line* N/A	MΩ	Line/Earth*	200
Confirmation that necessary inspections have been undeconfirmation of the adequacy of earthing			Insulation resi (In a polyphase Line	circuit, record the lov /Line* N/A eutral* N/A	MΩ MΩ		200 M
Confirmation that necessary inspections have been under Confirmation of the adequacy of earthing Confirmation of the adequacy of protective bonding			Insulation residence (In a polyphase Line Line/Ne RCD operating	circuit, record the low /Line* N/A eutral* N/A g time at	ME: ME: (if RCD fitted)	Line/Earth*	200 M
Confirmation that necessary inspections have been under Confirmation of the adequacy of earthing Confirmation of the adequacy of protective bonding Confirmation of correct polarity			Insulation residence (In a polyphase Line/Ne RCD operation RCD operation RCD operation Insulation I	circuit, record the lov /Line* N/A eutral* N/A g time at I	ME2 (if RCD fitted) if applicable	Line/Earth*	200 M
Confirmation that necessary inspections have been under Confirmation of the adequacy of earthing Confirmation of the adequacy of protective bonding Confirmation of correct polarity Circuit resistance R1 + R2 0.42	ertaken		Insulation residence (In a polyphase Line/Ne RCD operation RCD operation RCD operation Insulation I	circuit, record the low /Line* N/A eutral* N/A g time at	ME2 (if RCD fitted) if applicable	Line/Earth*	200 M
Confirmation that necessary inspections have been under Confirmation of the adequacy of earthing Confirmation of the adequacy of protective bonding Confirmation of correct polarity Circuit resistance R1 + R2 0.42	ertaken or R2 0.7		Insulation residence (In a polyphase Line/Ne RCD operation RCD operation RCD operation Insulation I	circuit, record the lov /Line* N/A eutral* N/A g time at I	ME2 (if RCD fitted) if applicable	Line/Earth* Neutral/Earth	200 M
Confirmation that necessary inspections have been under Confirmation of the adequacy of earthing Confirmation of the adequacy of protective bonding Confirmation of correct polarity Circuit resistance R1 + R2 0.42	ertaken or R2 0.7		Insulation residence (In a polyphase Line/Ne RCD operation RCD operation RCD operation Insulation I	circuit, record the lov /Line* N/A eutral* N/A g time at I	M(): M(): (if RCD fitted) if applicable	Line/Earth* Neutral/Earth	200 M
Confirmation that necessary inspections have been under Confirmation of the adequacy of earthing Confirmation of the adequacy of protective bonding Confirmation of correct polarity Circuit resistance R1 + R2 0.42	ertaken or R2 0.7		Insulation residence (In a polyphase Line Line/Net RCD operating RCD operating Confirmation	circuit, record the lov /Line* N/A eutral* N/A g time at lov g time at 5lon of correct polarity	M(2 M(2) (if RCD fitted) if applicable Instrument Sc	Line/Earth* Neutral/Earth erial No(s): 101397328	200 M
Confirmation that necessary inspections have been under Confirmation of the adequacy of earthing Confirmation of the adequacy of protective bonding Confirmation of correct polarity Circuit resistance R1 + R2	or R2 0.7 :		Insulation residence (In a polyphase Line/Net Line/Net RCD operating RCD operating Confirmation Risk asset	circuit, record the lov /Line* N/A eutral* N/A g time at 51 of correct polarity	M(2) M(2) (if RCD fitted) if applicable Instrument So	Line/Earth* Neutral/Earth erial No(s): 101397328 No. of pages	200 M
Confirmation that necessary inspections have been under Confirmation of the adequacy of earthing Confirmation of the adequacy of protective bonding Confirmation of correct polarity Circuit resistance R1 + R2	or R2 0.7		Insulation resign (In a polyphase Line Line Ne RCD operation RCD operation Confirmation Risk asset	circuit, record the low /Line* N/A eutral* N/A g time at 51.4n of correct polarity ssment appended:	M(): M(): (if RCD fitted) if applicable Instrument Solution ety of the existit	Line/Earth* Neutral/Earth erial No(s): 101397328 No. of pages ing installation, tha	200 Mmmmmmmmmmmmmmmmmmmmmmmmmmmmmmmmmmmm
Confirmation that necessary inspections have been under Confirmation of the adequacy of earthing Confirmation of the adequacy of protective bonding Confirmation of correct polarity Circuit resistance R1 + R2	or R2 0.7 : ceptions appended to detailed in Part 1	(γ) (γ) (γ) (γ) (γ) Ω (γ) Ω (γ)	Insulation residence (In a polyphase Line/Net RCD operation RCD operation Confirmation Risk assettificate, does BS 7671, american polyphase (Insulation Risk assettificate)	circuit, record the lov /Line* N/A gutral* N/A g time at 51 of correct polarity ssment appended: not impair the safe ded on the date s	M(): M(): (if RCD fitted) if applicable Instrument Solution ety of the existit	Line/Earth* Neutral/Earth erial No(s): 101397328 No. of pages ing installation, tha	200 Mmmmmmmmmmmmmmmmmmmmmmmmmmmmmmmmmmmm
Confirmation that necessary inspections have been under Confirmation of the adequacy of earthing Confirmation of the adequacy of protective bonding Confirmation of correct polarity Circuit resistance R1 + R2	or R2 0.7 : ceptions appended to detailed in Part 1 diverified in according to the BS 7671 except	(γ)	Insulation residence (In a polyphase Line Line/Net RCD operation RCD operation Confirmation Risk assettificate, does BS 7671, amend in Part 1 of the	circuit, record the lov /Line* N/A eutral* N/A g time at 51 of correct polarity ssment appended: not impair the safe nded on the date s his certificate.	M(): (if RCD fitted) if applicable Instrument Sizety of the existithown* and that	Line/Earth* Neutral/Earth erial No(s): 101397328 No. of pages ing installation, tha	200 Mmmmmmmmmmmmmmmmmmmmmmmmmmmmmmmmmmmm
Confirmation that necessary inspections have been under Confirmation of the adequacy of earthing Confirmation of the adequacy of protective bonding Confirmation of correct polarity Circuit resistance R1 + R2	or R2 0.7 : ceptions appended detailed in Part 1 diverified in according to the BS 7671 except esults of the inspections	(γ) (γ) (γ) (γ) Ω (γ) Ω (γ) Ω (γ) α	Insulation residence (In a polyphase Line Line/Net RCD operation RCD operation Confirmation Risk assettificate, does BS 7671, amend in Part 1 of the	circuit, record the lov /Line* N/A eutral* N/A g time at 51 g time at 51 of correct polarity ssment appended: not impair the safe nded on the date s his certificate. the Qualified Supervi	M(): (if RCD fitted) if applicable Instrument So ety of the existit hown* and that	Line/Earth* Neutral/Earth erial No(s): 101397328 No. of pages ing installation, that, to the best of my	200 M m m t the said wo knowledge a
Confirmation that necessary inspections have been under Confirmation of the adequacy of earthing Confirmation of the adequacy of protective bonding Confirmation of correct polarity Circuit resistance R1 + R2	or R2 0.7 : ceptions appended detailed in Part 1 diverified in according to the BS 7671 except esults of the inspections	(γ)	Insulation residence (In a polyphase Line Line/Net RCD operation RCD operation RCD operation Confirmation Risk assectificate, does BS 7671, amend in Part 1 of the ling reviewed by to Really signed by lan Michigan Really signed by land	circuit, record the lov /Line* N/A eutral* N/A g time at 51 n of correct polarity ssment appended: not impair the safe nded on the date s nis certificate. the Qualified Supervi	M(): (if RCD fitted) if applicable Instrument So ety of the existit hown* and that	Line/Earth* Neutral/Earth erial No(s): 101397328 No. of pages ing installation, that, to the best of my 4-Mar-17 f of (Trading Title of A	200 M m m t the said wo knowledge a
Confirmation that necessary inspections have been under Confirmation of the adequacy of earthing Confirmation of the adequacy of protective bonding Confirmation of correct polarity Circuit resistance R1 + R2	or R2 or R2 ceptions appended to the BS 7671 except ceptions of the inspective lan McIn	(γ)	Insulation residence (In a polyphase Line Line/Net RCD operation RCD operation RCD operation Confirmation Risk asset in Fart 1 of the Ingreviewed by the Michigan Michigan Michigan Residence (Ingreviewed by the Michigan Residence) and Ingreviewed by the Michigan Residence (Ingreviewed by the Michigan Residence) and Ingreviewed by the Michigan Residence (Ingreviewed by the Michigan Residence) and Ingreviewed by the Michigan Residence (Ingreviewed By the Ingreviewed B	circuit, record the lov /Line* N/A eutral* N/A g time at 51 g time at 51 of correct polarity ssment appended: not impair the safe nded on the date s his certificate. the Qualified Supervi	M(2) (if RCD fitted) if applicable Instrument So ety of the existithown* and that sor 2 For and on Behal	Line/Earth* Neutral/Earth erial No(s): 101397328 No. of pages ing installation, that, to the best of my 4-Mar-17 f of (Trading Title of A	200 M m m t the said wo knowledge a
Confirmation that necessary inspections have been under Confirmation of the adequacy of earthing Confirmation of the adequacy of protective bonding Confirmation of correct polarity Circuit resistance R1 + R2	or R2 O.7 ceptions appended detailed in Part 1 diverified in according to BS 7671 except esuits of the inspective lan McIn ITALS)	(γ)	Insulation resign (In a polyphase Line Line/Net RCD operating RCD operating RCD operating Confirmation Risk assettificate, does BS 7671, amend in Part 1 of the ling reviewed by to the Robert State of the Ro	circuit, record the lov /Line* N/A eutral* N/A g time at 51 g time at 51 of correct polarity ssment appended: not impair the safe nded on the date s his certificate. he Qualified Supervi	M(): (if RCD fitted) if applicable Instrument So ety of the existithown* and that sor For and on Behall Contract Heatin Address and Pc 2B Bankhead C	Line/Earth* Neutral/Earth erial No(s): 101397328 No. of pages ing installation, that, to the best of my 4-Mar-17 f of (Trading Title of A	200 M m m t the said wo knowledge a
Confirmation that necessary inspections have been under Confirmation of the adequacy of earthing Confirmation of the adequacy of protective bonding Confirmation of correct polarity Circuit resistance R1 + R2	or R2 0.7 : ceptions appended detailed in Part 1 detailed in accord th BS 7671 except esuits of the inspective lan McIn	(γ)	Insulation residence (In a polyphase Line Line/Net RCD operation RCD operation RCD operation Confirmation Risk assertificate, does BS 7671, american Melmonth of the Ingreviewed by the Melmonth of the Ingreviewed by the Ing	circuit, record the lov /Line* N/A eutral* N/A g time at 51 g time at 51 of correct polarity ssment appended: not impair the safe nded on the date s his certificate. he Qualified Supervi	M(): (if RCD fitted) if applicable Instrument S ety of the existithown* and that sor For and on Behal Contract Heatin Address and Pc 2B Bankhead C Edinburgh	Line/Earth* Neutral/Earth erial No(s): 101397328 No. of pages ing installation, that, to the best of my 4-Mar-17 f of (Trading Title of A	200 M m m t the said wo knowledge a
Confirmation that necessary inspections have been under Confirmation of the adequacy of earthing Confirmation of the adequacy of protective bonding Confirmation of correct polarity Circuit resistance R1 + R2	or R2 0.7 ceptions appended detailed in Part 1 diverified in accord th BS 7671 except esuits of the inspective lan McIn ITALS) Ature cion QS Elec	(γ)	Insulation residence (In a polyphase Line Line/Net RCD operation RCD operation RCD operation Confirmation Risk assertificate, does BS 7671, american Melmonth of the Ingreviewed by the Melmonth of the Ingreviewed by the Ing	circuit, record the lov /Line* N/A eutral* N/A g time at 51 g time at 51 of correct polarity ssment appended: not impair the safe nded on the date s his certificate. he Qualified Supervi	M(): (if RCD fitted) if applicable Instrument So ety of the existithown* and that sor For and on Behall Contract Heatin Address and Pc 2B Bankhead C	Line/Earth* Neutral/Earth erial No(s): 101397328 No. of pages ing installation, that, to the best of my 4-Mar-17 f of (Trading Title of A	200 M

NOTES FOR RECIPIENTS

THIS SAFETY CERTIFICATE IS AN IMPORTANT AND VALUABLE DOCUMENT WHICH SHOULD BE RETAINED FOR FUTURE REFERENCE

This safety certificate has been issued to confirm that the minor electrical installation work to which it relates has been designed, constructed, inspected, tested and verified in accordance with the national standard for the safety of electrical installations, British Standard 7671 (as amended) – Requirements for Electrical Installations (the IEE Wiring Regulations).

Where, as will often be the case, the existing installation incorporates a residual current device (RCD), there should be a notice at or near the main switchboard or consumer unit stating that the device should be tested at quarterly intervals. For safety reasons, it is important that you carry out the test regularly.

Also for safety reasons, the complete electrical installation including the minor electrical installation works which is the subject of this certificate will need to be inspected and tested at appropriate intervals by a competent person. NICEIC* recommends that you engage the services of an Approved Contractor for this purpose. There should be a notice at or near the origin of the existing installation (such as at the consumer unit or main switchboard) which indicates when the inspection of the complete installation is next due.

Only NICIEC Approved Contractor or Conforming Body responsible for the work is authorised to issue this NICEIC certificate.

If you were the person ordering the work, but not the owner or user of the installation, you should pass this certificate, or a full copy of it including these notes, immediately to the owner or user of the installation.

The "Original" certificate should be retained in a safe place and shown to any person inspecting, or undertaking further work on, the electrical installation in the future. If you later vacate the property, this certificate will demonstrate to the new user that the minor electrical installation works complied with the requirements of the national electrical safety standard at the time the certificate was issued.

The Minor Electrical Installation Works Certificate is intended to be used only for an addition or alteration to an existing circuit that does not extend to the provision of a new circuit. Examples include the addition of a socket-outlet or a lighting point to an existing circuit, or the replacement or relocation of a light switch. A separate certificate should have been received for each existing circuit on which minor works has been carried out. This certificate should be considered invalid if you requested the contractor to undertake more extensive work, for which an Electrical Installation Certificate or, if appropriate, a Domestic Electrical Installation Certificate should have been issued.

This certificate should not have been issued for electrical work in a potentially explosive atmosphere (hazardous area) unless the Approved Contractor holds an appropriate extension to NICEIC enrolment for such work.

Part 3 of the certificate is intended to facilitate the recording of information associated with the inspection and testing of the modified circuit, and the related parts of the existing installation on which the modified circuit depends for its safety. Generally each box should have been completed to confirm the results of a particular inspection or test by a "Yes" or a "\(\sigma\)", or by the insertion of a measured value. Where a particular inspection or test was not applicable, this should have been indicated by "N/A", meaning "Not Applicable". Where an inspection or a test was not practicable, the entry should read "LIM", meaning "Limitation", acknowledging that the particular circumstances prevented the particular inspection or test procedure from being carried out. In such a case, each limitation should have been recorded in the box entitled "Agreed limitations, if any, on the inspection and testing", together with the reason for each limitation.

Should the person ordering the work (eg the client, as identified on this certificate), have reason to believe that any element of the work for which the Approved Contractor has accepted responsibility (as indicated by the signature on this certificate) does not comply with the requirements of the national electrical safety standard (BS 7671), the client should in the first instance raise the specific concerns in writing with the Approved Contractor. If the concerns remain unresolved, the client may make a formal complaint to the NICEIC, for which purpose a standard complaint form is available on request.

The complaints procedure offered by NICEIC is subject to certain terms and conditions, full details of which are available upon application. NICEIC does not investigate complaints relating to the operational performance of electrical installations (such as lighting levels), or to contractual or commercial issues (such as time or cost).

*NICEIC is a trading name of NICEIC Group Limited, a wholly owned subsidiary of The Electrical Safety Council. Under licence from The Electrical Safety Council, NICEIC acts as the electrical contracting industry's independent voluntary regulatory body for electrical installation safety matters throughout the UK, and maintains and publishes registers of electrical contractors that it has assessed against particular scheme requirements (including the technical standard of electrical work)

For further information about electrical safety and how NICEIC can help you, visit www.niceicgroup.com



Install | Service | Repair

We can now carry these out at the time of doing other safety checks in your property

Client

ID 3378

Property

ID 85210

Miss S Podarama

30 Meadow Craigour

Edinburgh Midlothian

EH17 7SB

17 Nether Craigour Edinburgh

Midlothian

EH17 7SB

G Clark

They is the Record not

Invoice Details

Job ID

364342

Cient Ref. Mrs Podarama

Inv. No. 302424

INVOICE PAID RECEIPT

Visit Detail

<u>Date</u>	<u>Eng</u>	Work Description
15-Mar-17	33	Carried out fault finding and carried out EICR.
15-Mar-17	38	Upgrade smoke alarms
18-Mar-17	32	Carried out QA
23-Mar-17	33	Rectified remedial work.

Labour Charges

<u>Qty</u>	Labour Description		Cost
8	Electrical Remedial Work		£520.00
		Labour Total	£520.00

Part Charges

Qty	Part Description		Cost
1	Materials		£210.00
		Parts Total	£210.00
THAN	YOU FOR PAYING THIS INVOICE	Total Amt	£730.00
PAY IN	ID 0	Credit Amt	£0.00
PAID E	Y	Sub Total	£730.00
PAY R	EF.	VAT	£146.00
RCD D	ATE	Inv Total	£876.00









MINOR ELECTRICAL INSTALLATION WORKS CERTIFICATE

Certificate No. 243201773547-335

Install | Service | Repair

NICEIC Enrolment Number

031779

Issued in accordance with British Standard 7671-Requirements for Electrical Installations by an Approved Contractor or Conforming Body enrolled with NICEIC, Warwick Hall Park, Houghton Regis, Dunstable LU5 5ZX

To be used only for minor electrical work which does not include the provision of a new circuit

PART 1: DE	TAILS OF THE MINOR WORKS				Details of depa	ortures, if a	ny, fron	n BS 7671 (as a	mmended):		
Client: Po	darama										
Date minor w	orks completed: 24-Mar-17	,									
Description of	the minor works:				Location/addre	ess of the n	ninor w	orks:			
Replaced Kitcl						Nether C					
replaced Kitch	nen nghe					Edinburg	h				
						Midlothia	าก				
						EH17 7SE	3				
PART 2: D	ETAILS OF THE MODIFIED CIRCU	JIT									
System type a	and earthing arrangements:		TN-C-S	_ т	N-S Π	☐ TN-	c [] IT 🗌			
	easures against electric shock:			ADS							
	protective device for modified circui	it:	BS(EN)	60898		Туре	В	Ra	ating 6		Α
	ent device (if applicable):		BS(EN)			Туре			I _{Au}		mA
	ing system used to	NC	121		rence	rsa of	lives 1	.0 mm²	csa of cpc 1.0	,	mm²
modify the ci	ircuit:	VC			ethod A	C3a O1	11463 1				
	neasure for protection against electr n time permitted by BS 7671:	ic shock is ADS,	insert maxi	num	0.4		Maxin	num Zs permitt	ed by BS 7671		Ω
	f any, on exisiting installation, includ	ling adequacy o	of earthing a	nd bond	ing arrangement	ts (see Reg	ulation	132.16):			
None	, , , , , , , , , , , , , , , , , , , ,										
Confirmatio	on that necessary inspections have b	een undertake	_	V (1)				ver or lowest valu	ue, as appropriate) Line/Earth*	200	M£
Confirmatio	on of the adequacy of earthing			· (1)							ME
Confirmation	on of the adequacy of protective bor	nding		(1)		utral* N/A	tioned.	WE	Neutral/Earth	200	
Confirmation	on of correct polarity				RCD operating	g time at	l _{du}	(if RCD fitted)			ms
Circuit resis	tance R1 + R2 0.53	Ω	or R2	Ω	RCD operating	g time at	5l∆n	if applicable			ms
Maximum r	measured earth fault loop impedance	ce, Zs	0.88	Ω	Confirmation	of correct	polarity			✓	(·
Agreed limit	tations, if any, on the inspection and	testing:						Instrument S	erial No(s):		
None									101397328		
PART 4:	DECLARATION Details of perm	nittd exception	s appended:		Risk asses	sment app	ended:		No. of pages		
	at the minor electrical installation w							tv of the exisiti	ng installation, that	the said	d work
have been o	at the minor electrical installation w designed, constructed, inspected, te e time of inspection, the works com	sted and verifie	ed in accorda	nce with	i BS 7671, amen	dea on the	date st	nown* and that	t, to the best of my	knowled	lge an
belief, at the	e time of inspection, the works com	The results of	the inspection	and test	ing reviewed by th	ne Qualified	Supervis	sor * 2	4-Mar-17		
Name	Ben Miller	Name	lan McInt						of (Trading Title of Ap	proved C	:ontract
(CAPITALS)	O 1.7/1	(CAPITALS)						Contract Heatir	ig Ltd.		
	You Mills		1 Me	2	grade appending on humania to provide the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control o		,	Address and Po	stcode		
Signature	er / ruo/	Signature		× .				2B Bankhead C	rossway South		
Position	Electrician	Position	QS Electr	ician				Edinburgh Midlothian			
Date	24-Mar-17	Date	25/03/17					EH11 4EX			